Technical data sheet 2923 sialoX



Status:	Ok
Approval:	24.11.2023

Classification	Public series
Product type:	Coated abrasives
Main industries:	General Fabrication
Further industries:	Containers Casting and Forging Machinery, equipment Tubes and Profiles Stamped and Shaped Parts Turbines

Product profile			
Grit type:	Aluminium oxide		
Grit range (total):	40; 60-80; 120-150; 240	FEPA P / ISO 6344	
Backing:	X-wt cloth		
Coating:	Closed		
Bonding:	Resin over resin		
Special coating:			
Equipment:			

Properties		Technology
Removal rate:	5 - Medium	
Lifetime:	6 - Medium	
Finishing:	7 - good	
Flexibility:	5 - Medium	
Contact pressure:	5 - Medium	

Advantages	
General Fabrication:	 Wide range of applications Excellent price/performance ratio Universal product for all metals Highly flexible, ideal for hard to reach areas Versatile all-round product with an attractive range of options

Applications	
General Fabrication:	 Deburring Removal of rust and paint Welded seam preparation Stock removal Removal of discolouration Surface treatment Smoothing and blending of flaws



Material		
General Fabrication:	Non-ferrous metals	 Non-ferrous metal
	Steel	 Unalloyed / low-alloy steel

Conversion forms	Upper conversion	Lower conversion
d	Flap wheel	- Flap wheel with shaft cloth
	Belts	- spiralbands

Application	Superordinate group	Subgroup
	Portable machine sanding	Straight grinder
Cut:		

Details	
No suitability for:	- Wet sanding
Sanding recommendation:	
Safety recommendation:	Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Follow the general FEPA safety recommendations - Use eye and face protection - Use hearing protection - Spectacles - glove - Use an effective dust extraction unit or wear a fine dust mask

Communication				
Claim:	The dependable series for grinding of unalloyed and non-ferrous steel			
Сору:	As a cost-effective abrasive with a stable cloth backing, 2923 sialoX offers aggressive finish, good tear resistance and particularly long service life in a variety of applications including final grinding of unalloyed steel and non-ferrous metals.			
Image material:	Product Top View (PTV)	Front side: Rear side:	ID ID	
	Application image	General Fabrication:	ID 8657	
	Product show:			
	Macro shot:			
	Packaging image:			
	Product group image:		ID 12294	

Main applicationSecondary application