



1950 siaspeed

For a perfect finish at full speed



For a perfect finish at full speed

The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.

- A versatile all-round product
- High performance for stock removal
- Longest lifetime
- Minimal clogging thanks to open coating in 220 600 grit range

Product profile

Grit type: Mixed grit with ceramic 40 - 80

content

Semi-friable aluminium P100 - P400

oxide / blue-fired

White aluminium oxide P500 - P1500

Grit range: 40; 60-1500

Backing: Paper (FSC-certified) 40 - P600

Film P800 - P1500

Electrostatic 40 - P180 Coating: Electrostatic open P220 - P600

> P800 - P1500 Special process

Bonding: Resin over resin

from 80 Special coating: Stearate

Applications

- Keying or sanding surfaces
- Sanding off old paint and varnish
- Keying smoothed surfaces
- Fine sanding of surfaces
- Flatting uneven areas

Materials

Lacquer; Hard wood; Soft wood; Solid surface material; Primer filler; Bodyfiller; Resinous wood; Plaster; Dry wall lining boards; **Plastics**

Technology

Open coating; Plain; S Performance; siafast; siasoft

Use













