



1944 siaone

the one with cut



the one with cut

The quality with aggressive cut and optimum lifetime. For price-conscious users for working with various materials, for example: bodyfiller, primer filler, varnish, paint and wood.

- ▶ Aggressive initial sanding thanks to optimised sanding grain
- ▶ Process stability thanks to uniform scratch depths in all grits
- ▶ Excellent price/performance ratio

Product profile

| | | |
|------------------|-----------------------------|-------------|
| Grit type: | Aluminium oxide | P040 – P500 |
| Grit range: | 40; 60-240; 320; 400-500 | |
| Backing: | c-wt paper (FSC-certified) | P040 – P100 |
| | b-wt paper (FSC-certified) | P120 – P500 |
| Coating: | Electrostatic | |
| Bonding: | Resin over resin | |
| Special coating: | Stearate | P220 – P500 |

Use



Applications

- Sanding of coatings and impurities
- Keying of primers
- Flattening of bodyfiller and primer filler
- Fine sanding of primer filler
- Keying of old and new lacquers

Materials

Colour; Primer filler; Lacquer; Old lacquer; Primer coat; Epoxy primer coat; Plastics; Acrylic glass; Gelcoat polyester; Glass-fibre reinforced plastic (GRP); Composite

Technology

siafast