



1919 siawood for hand and handmachine sanding

The controlled scatter process, temperature and humidity-resistant backing and anti-static properties, resulting from the innovative production process, combine to produce outstanding sanding results and superb quality of the surface finish.

The 1919 siawood TopTec series is ideal for both hand and machine sanding and opens up new possibilities of achieving extremely efficient and consistent material removal rates.

Structure

Grit:	semi-friable aluminium oxide	P040 - P220
Coating:	electrostatic open	P040 - P120
	electrostatic closed	P150 - P220
Bonding:	synthetic resin	
Backing:	f-wt paper	
Grit range:	P040 - P220	

Properties

Removal rate:	very high
Lifetime:	very long
Stability:	very strong
Application:	hard

Advantages

- ☑ Very high performance in heavy-duty applications
- ☑ Robust backing and high-strength grit bonding for long life
- ☑ Controlled scattering ensure a perfect surface quality
- ☑ Fast and safe change of abrasive with siafast hook and loop fastening system
- ☑ Shape-retaining, temperature and humidity-resistant backing
- ☑ Latest generation anti-static equipment



siafast

1919 siawood TopTec is also available with the siafast hook and loop fastening system, allowing a fast and safe change of the abrasive.

Orbital sander



Sanding off paint and varnish	P040 - P080
Keying of paint and varnish	P100 - P150
Coarse sanding of solid wood	P040 - P080
Fine sanding of solid wood	P100 - P220
Keying of primers and fillers	P100 - P220

Random orbital sander



Sanding off paint and varnish	P040 - P080
Keying of paint and varnish	P100 - P150
Coarse sanding of solid wood	P040 - P080
Fine sanding of solid wood	P100 - P220
Keying of primers and fillers	P100 - P220

Angle grinder



Sanding off paint and varnish	P040 - P150
Removal of rust spots on metal	P040 - P150